

ARACO MASONRY FIX

One-Component Ready-mixed Cementitious Mortar

Product Description

ARACO MASONRY FIX is a ready to use mortar for mounting hollow blocks, bricks, stones and general filler between concrete and bricks.

ARACO MASONRY FIX is a development of typical properties of the pre-mixed mortar meets the requirements of BS EN 1881 part 207 & BS EN 196-1-1994

Applications

ARACO MASONRY FIX is recommended for mounting hollow blocks and general filling mortar: -

- Mounting Hollow Blocks
- Mounting Stones
- Mounting Bricks
- Filling Mortar.

Product Advantage

- One-component
- Improved workability and water retention
- Good bond strength.

Surface Preparation

Substrate must be clean and free of all foreign or contaminating materials such as oils, grease, silt, and dust, loose aggregate or sand particles. It is highly recommended to moisten the surfaces with a water spray bottle before applying **ARACO MASONRY FIX**.



Package: 50 Kg Bags

Consumption: 20 kg/m² per 1 cm THK

Product Application

Mix ARACO MASONRY FIX with 6-7 liters of clean cool water mix with an electric drill with low rotation speed (300rpm). Mix with a slow speed drills until a lump free homogeneous paste is obtained.

Curing

After application, Cure with water for three days by spraying 3 to 4 times daily.

Technical Data

Pull off test

Standard conditions @ 28 days	0.3 MP	EN BS 1881 part 207
-------------------------------	--------	---------------------

Compressive Strength

Average strength at 28 days	13 MPa	EN BS 196-1-1994
-----------------------------	--------	------------------

Tensile Strength

Average strength at 28 days	5.14 Mpa	BS 6319-7
-----------------------------	----------	-----------

Density Powder	1.95 kg/L
----------------	-----------

Grain size	4 mm
------------	------

Thickness	1-2 cm
-----------	--------

Product Data

Composition	Selected grades of sand, special cement and additives.
-------------	--

Appearance	Grey Powder
------------	-------------

Storage condition	Store in a dry area between 5°C and 35°C. Protect from direct sunlight
-------------------	--

Shelf Life	12 months minimum from production date if stored properly in original an opened packaging
------------	---

Safety Instructions

The product may cause skin irritation. Wear gloves and goggles and apply barrier cream to your hands. In contact with eyes or mucous membrane. flush immediately with plenty of warm water and seek medical attention without delay.

Legal Notes

The information, recommendations, and application are based on ARACO current knowledge and experience of the products when properly stored, handled, and applied under normal conditions. ARACO products are guaranteed against defective materials and manufacture and sold subject to standard conditions. Users should always refer to the most recent technical data sheet for the product concerned, copies of which will be supplied on request.

More from ARACO

A wide range of construction chemical products is manufactured by ARACO which include:

- Premixed mortar
- Tile adhesives & Grout
- Concrete Repair
- Flooring systems
- Protective Coating
- Waterproofing
- Bonding Agents
- Concrete Admixtures
- Surface Treatments
- Grout & Anchors
- Sealants
- Sports Flooring