

ARACO WPR 78

Impregnating Agent; Water Repellent

Product Description

ARACO WPR 78 is used as hydro-repellent protection for adsorbent construction materials as: concrete masonry, fiber concrete panels, brick masonry, silico-calcareous bricks, natural or artificial stones, cellular piling, plastering and mineral paintings, etc. It can be used also as a primer for external paints and it is also effective for wet substrates without effecting the color of stone surface.

ARACO WPR 78 is highly effective solvent base water repellent with unique properties and extra durability.

Applications

ARACO WPR 78 is used as water repellent for: -

- Various types of concrete
- Natural and mineral stones
- Bricks
- Render applications
- Tile grout
- Primer for paints application.
- Ceramic, porcelain and marble

Product application

ARACO WPR 78 must be used on clean, sound, free of contaminants and dry, in order to avoid an insufficient penetration and therefore the effectiveness of the treatment. The treatment is run by immersion, with a brush or by spraying. Surface must be treated twice while the first layer is still wet.

Technical Data

Test	Value
Density	1 ± 0.01
Appearance	Transparent liquid

Safety Instructions

The product may cause skin irritation. Wear gloves and goggles and apply barrier cream to your hands. In contact with eyes or mucous membrane. flush immediately with plenty of warm water and seek medical attention without delay.



Package: 5, 10, 20, 200 lt.

Consumption: 0.3-0.6 liter/m²/ 2 coats

Product Data

Composition	Solvent base silane siloxane
Storage condition	Store in a dry area between 5C and 35C. Protect from direct sunlight
Shelf Life	12 months minimum from production date if stored properly in original unopened packaging.

Legal Notes

The information, recommendations, and application are based on ARACO current knowledge and experience of the products when properly stored, handled, and applied under normal conditions. ARACO products are guaranteed against defective materials and manufacture and sold subject to standard conditions. Users should always refer to the most recent technical data sheet for the product concerned, copies of which will be supplied on request.