



ARACO ZR 130

Zinc Rich EPOXY Coating Anti-Corrosion Primer for Steel.

Product Description

ARACO ZR 130 is a two component, and solvent based epoxy used to provide the highest protection against corrosion of iron and steel.

ARACO ZR 130 it's also used to protect exposed steel reinforcement against rust and to obtain higher bond between steel and concrete.

Applications

ARACO ZR 130:

- is used to protect steel reinforcement against rust and to obtain higher bond between steel and concrete.
- steel bridges, trusses and steel structure.
- steel pipes

Product Advantages

- Prevent corrosion and rust of steel
- Adheres firmly to steel surface.
- Epoxy modified Zinc with Zinc content ⁵ 40 %
- Applies with brush or roller
- High resistant to water, salt and chemicals.

Surface Preparation

- Surfaces should be free of rust, dust, oil and grease.
- the two components of ARACO ZR 130 should be mixed together directly prior to applications by brush or roller
- when required to apply 2 coats of ARACO
 ZR 130, the second coat must be applied after a minimum 12 hr. after the first coat at 25 °C



Package: 1 K G & 5 KG

Consumption: 0.25 L/m²/2 Coat.

Technical Data

Test	Value
Density	1.75±0.1
Drying Time	9 Hours @ 23 °C
Pot Life	3 Hours @ 23 °C
Thickness	150 microns.
Solid content by weight	65 %
Curing Time	4 – 7 days for curing





Product Data

Туре	Solvent based chemical
Form	Two component liquid
Color	Grey
Storage condition	Store in a dry area between 5C and 35C. Protect from direct sunlight
Shelf Life	12 months minimum from production date if stored properly in original unopened packaging.

Safety Instructions

The product may cause skin irritation. Wear gloves and goggles and apply barrier cream to your hands. In contact with eyes or mucous membrane. flush immediately with plenty of warm water and seek medical attention without delay.

Legal Notes

The information, recommendations, and application are based on ARACO current knowledge and experience of the products when properly stored, handled, and applied under normal conditions. ARACO products are guaranteed against defective materials and manufacture and sold subject to standard conditions. Users should always refer to the most recent technical data sheet for the product concerned, copies of which will be supplied on request.

More from ARACO

A wide range of construction chemical products is manufactured by ARACO which include:

- Premixed mortar
- Tile adhesives & Grout
- Concrete Repair
- Flooring systems
- Protective Coating
- Waterproofing
- Bonding Agents
- Concrete Admixtures
- Surface Treatments
- Grout & Anchors
- Sealants
- Sports Flooring





