

ARACO Elast Bit Coat

Water based elastomeric latex rubberized bitumen Coating

Product Description

ARACO ELAST BIT COAT is a dark black emulsified bitumen liquid reinforced with latex rubber, formulated from selected raw materials to forms a flexible and continuous water proofing and protective coating.

Uses

ARACO ELAST BIT COAT Primer can be used:

- Interior and exterior areas for vertical and horizontal applications from the direction of coming water
- For waterproofing on roofs, insulations with felt, and asphalt, lead, zinc, aluminum, concrete, light concrete, wooden, slate, wavy sheet surfaces.
- Retaining walls
- Waterproofing of main curtains and culverts
- Insulation of parts of artworks under the soil against water and moisture
- Suitable for use as curing compound for fresh concrete
- Where minor live cracks may occurs in concrete

Product Advantages

- One Component
- Forms seamless, permanent, moisture and water proof coating.
- Resistant to chemicals and salt solution in the soil.
- Resistant to freeze-thaw cycle.
- Does not contain solvents and it is environmental friendly



Package: 15 liters pail

Consumption: approx. 3m² /liter

Surface Preparation

Substrate should be sound, clear, free from loose material, grease, laitance, dirt curing compound, etc. Surfaces must be dry, even and smooth and any imperfections should be repaired by the means of ARACO REPAIR SYSTEM.

Application

ARACO ELAST BIT COAT can be stirred and applied using a brush or a spray. It is recommended to apply a minimum of two coats of **ARACO ELAT BIT COAT**. A thick coat can be laid even on vertical surface due to the thixotropic nature of the product. Each layer should be applied at right angle to the previous one to obtain proper uniform coverage. Allow a minimum of three hours between coats. In high humidity and cold weather, this period can extend up to 12 hours.

Do not apply in wet weather or in direct sunlight.

Product Data

Color	Viscous Black liquid
Density	1.1±0.1 g/cm ³
PH	10
Over coating	12 hr
Toxicity	Non toxic
VOC	<25g/ltr
Tensile Strength	>0.5 Mpa
Tear Strength	0.2 Mpa
Application Temp	-30°C and 100°C.
Storage life	Store in a dry shaded area at temperature between 10°C and 40°C.
Shelf Life	Original Sealed container has a shelf life of 12 months if stored in the right conditions

Safety Instructions

The product may cause skin irritation. Wear gloves and goggles and apply barrier cream to your hands. In contact with eyes or mucous membrane. flush immediately with plenty of warm water and seek medical attention without delay.

Legal Notes

The information, recommendations, and application are based on ARACO current knowledge and experience of the products when properly stored, handled, and applied under normal conditions. ARACO products are guaranteed against defective materials and manufacture and sold subject to standard conditions. Users should always refer to the most recent technical data sheet for the product concerned, copies of which will be supplied on request.

More from ARACO

A wide range of construction chemical products is manufactured by ARACO which include:

- Premixed mortar
- Tile adhesives & Grout
- Concrete Repair
- Flooring systems
- Protective Coating
- Waterproofing
- Bonding Agents
- Concrete Admixtures
- Surface Treatments
- Grout & Anchors
- Sealants
- Sports Flooring