



ARACO ACTIVE L

Waterproofing Concrete Admixture

ProductDescription

ARACO ACTIVE L is a high range water reducer waterproofing admixture based on modified polymers technology

Standard Compliance

- ASTM C-494 Types A and D

Applications

ARACO ACTIVE L is recommended for use in structural and mass concrete, particularly for water-retaining structures such as:

- Sewage Tanks
- Roof Slabs
- Rendering
- Canals
- Reservoir and Dams
- Culvert

ProductAdvantages

- Improved workability without increased water content
- Improved water tightness
- Reduced shrinkage
- Allows easier compaction leading to denser concrete and superior finish
- Chloride free - does not attack reinforcement.

ProductData

Characteristics

Composition	Water soluble biopolymers
Appearance	Brown liquid
Specific Gravity	1.06 ±0.03
Chloride Content	Nil
Storage Condition	Store In a dry shaded condition, at temperature between 5°C and 35°C
Shelf Life	Original sealed package has a shelf like of 12 months if stored properly.



ARACO ACTIVE L

PACKAGE	25 lt. or 200 lt drums. 1000 liter
DOSAGE	0.5 to 1.5% by cement weight

Safetyinstructions

Product may cause skin irritation. Wear gloves and goggles and apply barrier cream to hands. In contact with eyes or mucous membrane, flush immediately with plenty of warm water and seek medical attention without delay.

Legalnotes

The information, recommendations and application - based on ARACO current knowledge and experience of the products when properly stored, handled and applied under normal conditions. ARACO products are guaranteed against defective materials and manufacture and are sold subject to its standard conditions. Users should always refer to the most recent Technical Data Sheet for the product concerned, copies of which will be supplied on request.

ARACOFORBUILDINGMATERIALSANDCONTRACTING

Egypt, Tel:+0228605490–Fax:+0228605491

Email:aracoegypt@grouparaco.com

ARACO ACTIVE L