

Polycarboxylate superplasticizer and retarding Admixture

Product Description

ARACO PC10 is a new generation super high range water reducing and retarding admixture with a unique formulation based on carboxylated polymers technology.

ARACO PC10 does not contain calcium chloride or any other intentionally added chlorides and will not initiate or contribute to corrosion on steel reinforcement present in the concrete.

Standard Compliance

- ASTM C-494 Type G

Applications

ARACO PC10 is recommended for use:

- The production of high strength concrete products.
- Where high strength are desired
- A high workability with low water cement ration

Advantages

- High workability of placing and compaction without segregation
- Higher early and ultimate strengths for cost effective high strength concrete
- Higher early strengths allow faster demolding and more efficient use of forms of precast
- Improves pumpability in conjunction with setting time
- Increased slump improves workability and reduces labor costs.
- Full flow action aids in pumping and reduces need for vibration.
- Greater concrete density reduces permeability and increases durability.
- High resulting workability recommended for congested reinforced structures
- Recommended for mass concrete

Characteristics

Composition	Polycarboxylate Ether
Appearance	Light Yellow liquid
Specific Gravity	1.10 ± 0.015
Chloride Content	Nil
Storage Condition	Store In a dry shaded condition, at temperature between 5°C and 35°C
Shelf Life	Original sealed package has a shelf like of 12 months if stored properly.



ARACO PC10

PACKAGE	1000 lt. flow bins Bulk
DOSAGE	0.4 to 2 % /100 kg

Carry on the trial mixes to obtain the correct dosage

Safety instructions

Product may cause skin irritation. Wear gloves and goggles and apply barrier cream to hands. In contact with eyes or mucous membrane, flush immediately with plenty of warm water and seek medical attention without delay.

Legal notes

The information, recommendations and application - based on ARACO current knowledge and experience of the products when properly stored, handled and applied under normal conditions. ARACO products are guaranteed against defective materials and manufacture and are sold subject to its standard conditions. Users should always refer to the most recent Technical Data Sheet for the product concerned, copies of which will be supplied on request.