



ARACO PC104 F

Polycarboxylate superplasticizer

Product Description

ARACO PC104 F is a new generation high range water reducing admixture with a unique formulation based on carboxylated polymers technology.

ARACO PC104 F does not contain calcium chloride or any other intentionally added chlorides and will not initiate or contribute to corrosion on steel reinforcement present in the concrete.

Standard Compliance

- ASTM C-494 Types F

Application

ARACO PC104 F is recommended to be used:

- in the production of all high strength Concrete products, whenever high plasticity and increase early and ultimate strengths are desired
- High workability at low water cement ratios is required

Advantages

- High workability of placing and compaction without segregation
- Higher early and ultimate strengths for cost effective high strength concrete
- Higher early strengths allow faster demolding and more efficient use of forms of precast
- Improves pumpability in conjunction with setting time
- Increased slump improves workability and reduces labor costs.
- Full flow action aids in pumping and reduces need for vibration.
- Greater concrete density reduces permeability and increases durability.
- Recommended for mass concrete

Characteristics

Composition	Polycarboxylate Ether
Appearance	Light Yellow liquid
Specific Gravity	1.04 ± 0.015
Chloride Content	Nil
Storage Condition	Store In a dry shaded condition, at temperature between 5°C and 35°C
Shelf Life	Original sealed package has a shelf like of 12 months if stored properly.



ARACO PC104 F

PACKAGE 1000 lt. flow bins Bulk

DOSAGE 0.2 to 1.5% by weight

Carry on the trial mixes to obtain the correct dosage

Safety instructions

Product may cause skin irritation. Wear gloves and goggles and apply barrier cream to hands. In contact with eyes or mucous membrane, flush immediately with plenty of warm water and seek medical attention without delay.

Legal notes

The information, recommendations and application - based on ARACO current knowledge and experience of the products when properly stored, handled and applied under normal conditions. ARACO products are guaranteed against defective materials and manufacture and are sold subject to its standard conditions. Users should always refer to the most recent Technical Data Sheet for the product concerned, copies of which will be supplied on request.

ARACOFORBUILDINGMATERIALSANDCONTRACTING

Lebanon, Beirut: Fax: +961 8 512413/ Tel:+9611562510