Polycarboxylate superplasticizer and retarding Admixture

ProductDescription

ARACO PC106 is a new generation high range water reducing and retarding admixture with a unique formulation based on carboxylated polymers technology.

ARACO PC106 does not contain calcium chloride or any other intentionally added chlorides and will not initiate or contribute to corrosion on steel reinforcement present in the concrete.

Standard Compliance

ASTM C-494 Type G

Applications

ARACO PC106 is recommended for use in the production of all high strength concrete products, whenever high plasticity and increase early and ultimate strengths are desired.

The superplasticizing action of **ARACO PC106** provides excellent workability at low water cement ratios

ProductAdvantages

- High workability of placing and compaction without segregation
- Higher early and ultimate strengths for cost effective high strength concrete
- Higher early strengths allow faster demolding and more efficient use of forms of precast
- Improves pumpability in conjunction with setting time
- Increased slump improves workability and reduces labor costs.
- Full flow action aids in pumping and reduces need for vibration.
- Greater concrete density reduces permeability and increases durability.
- High resulting workability recommended for congested reinforced structures
- Recommended for mass concrete

Characteristics

Composition Polycarboxylate Ether

Appearance Yellow Liquid

Specific Gravity 1.06 ±0.015

Chloride Content Nil

Storage Condition Store In a dry shaded

condition, at temperature

between 2°C and 50°C

Shelf Life Original sealed package has

a shelf like of 12 months if

stored properly.



ARACO PC106

PACKAGE 1000 lt. flow bins Bulk

DOSAGE 0.2 to 2.5% by weight

Carry on the trial mixes to obtain the correct dosage

Safetyinstructions

Product may cause skin irritation. Wear gloves and goggles and apply barrier cream to hands. In contact with eyes or mucous membrane, flush immediately with plenty of warm water and seek medical attention without delay.

Legalnotes

The information, recommendations and application - based on ARACO current knowledge and experience of the products when properly stored, handled and applied under normal conditions. ARACO products are guaranteed against defective materials and manufacture and are sold subject to its standard conditions. Users should always refer to the most recent Technical Data Sheet for the product concerned, copies of which will be supplied on request.

ARACOFORBUILDINGMATERIALSANDCONTRACTING

Lebanon, Beirut: Fax: +961 8 512413/ Tel:+9611562510