



ARACO EPO REP PLUS

Three Component High Strength Epoxy Resin Patching Mortar

Product Description

ARACO EPO REP PLUS is a three thixotropic component, epoxy based, thixotropic, solvent-free, and selected aggregates.

ARACO EPO REP PLUS is used as a repair or patching mortar for many mineral substrates such as concrete, cementitious materials and stones.

The thixotropic nature of **ARACO EPO REP PLUS** allows it to function in vertical and over-headed situation without sagging while maintaining excellent bond.

Uses

ARACO EPO REP can be used:

- to repair purposes
- As a filler mortar
- to restore profile of precast concrete
- To restore profile of cast in place concrete
- As an abrasion and impact resistant coating

Advantages

- High tensile and flexural strength
- Non toxic
- High resistance to moisture
- High abrasion and impact resistance
- High early Strength
- Chemical resistance

Product Data

Component	A : Resin B : Hardener C: Aggregate
Appearance	Greyish mortar
Density	1.9 ± 0.05
Flexural Strength	30 Mpa (7days)
Tensile Strength	15 MPa(7 Days)
Compressive Strength	70 Mpa(7 days)
Storage Condition	Store in a dry area between 5°C and 30°C. Protect from direct sunlight
Shelf Life	2 years minimum from production date if stored properly in original unopened packaging.



ARACO EPO REP PLUS

Package 10 Kg

Application Rate 2 kg/ mm²

Priming

Before the application of ARACO EPO REP PLUS, it is recommended to primer the surface with ARACO EPO REP PRIME for better result. (REFER TO ARACO TDS)

It is possible to apply ARACO EPO PLUS without priming the surface.

Mixing

ARACO EPO REP PLUS is made up of three components (A: resin, B: Hardener, C: Selected Aggregates) supplied pre-weighted in the correct proportions. Under no circumstances should part mixing be carried out.

Stir Part A using a mechanical means for about 1 min. Pour part B into part A and mix them for about 3 min at a low speed until a uniform color is achieved. Once a uniform color is obtained, Start adding Part C to the mix slowly until a well distribution of aggregates is obtained.

Application

Apply **ARACO EPO REP PLUS** by a trowel, or a float. It is recommended to compact well the materials.

Make sure that the overall layer of the layer is not less than 3 mm.

ARACO FOR ADMIXTURES & CONSTRUCTION MATERIALS S.a.l.

Lebanon, Beirut: Fax: +961 8 512413/ Tel:+961 1 562510

Email: aacm@araco-group.net / MOB:+961 3 104539



ARACO EPO REP PLUS

Three Component High Strength Epoxy Resin Patching Mortar

Safety instructions

Product may cause skin irritation. Wear gloves and goggles and apply barrier cream to hands. In contact with eyes or mucous membrane, flush immediately with plenty of warm water and seek medical attention without delay.

Legal notes

The information, recommendations and application - based on ARACO current knowledge and experience of the products when properly stored, handled and applied under normal conditions. ARACO products are guaranteed against defective materials and manufacture and are sold subject to its standard conditions. Users should always refer to the most recent Technical Data Sheet for the product concerned, copies of which will be supplied on request.

ARACO FOR ADMIXTURES & CONSTRUCTION MATERIALS S.a.l.

Lebanon, Beirut: Fax: +961 8 512413/ Tel:+961 1 562510

Email: aacm@araco-group.net / MOB:+961 3 104539