



# ARACO SEAL-CRETE

## High solids acrylic floor and wall sealer and curing compound

### Product Description

**ARACO SEALCRETE** is a high solid floor and wall sealer, dust proofer and curing compound based on solvent borne acrylic resin.

**ARACO SEALCRETE** is ideal for using internally and externally over decorative plasters, masonry surfaces, stamped concrete and concrete floors in light to medium duty trafficable areas.

**ARACO SEALCRETE** is also used as a curing compound and sealer for freshly placed concrete to retain sufficient moisture to ensure full hydration of the cement.

### Standard Compliance

- ASTM C309, Type I, Class A and B,
- ASTM C1315, Type I, Class A.
- EN 13813

### Applications

**ARACO SEALCRETE** is suitable to be use on the following substrate:

- Cement
- Acrylic
- Bitumen
- Emulsion
- Epoxy resin based products.

### Product Advantages

- Durable finish that seals concrete and natural stone surfaces
- Prevent the penetration on of oils and liquids.
- Abrasion enhancement
- Improves concrete and mortar curing
- Cost effective

### Characteristics

Color	Clear
Density	1 g/cm <sup>3</sup>
Viscosity	1.2 poise
Tack free time	50 min
Time between coats	36 hr
Bond strength	5 Mpa
Water Retention	>80%
Voc	<600 g/ltr
Storage Condition	Store in a dry area between 5°C and 35°C. Protect from direct sunlight
Shelf Life	6 months minimum from production date if stored properly in original unopened packaging.



### ARACO SEALCRETE

PACKAGE	5-20-200 liters
CONSUMPTION	8-10 m <sup>2</sup> /liter

### Surface Preparation

The substrate must be sound, clean, dry, even, dense and free from oil, grease, dust and other contaminants.

A clean surface will ensure maximum adhesion between the substrate and the coating. Unsound layers and contaminated concrete surfaces must be prepared using mechanical surface removing equipment.

Areas contaminated with oil or grease, should be treated with hot compressed air.

### Product Application

Apply **ARACO SEALCRETE** using brush or roller, or airless spray machine. It is recommended to apply 2 coats of **ARACO SEALCRETE** on the concrete.

### Safety instructions

Product may cause skin irritation. Wear gloves and goggles and apply barrier cream to hands. In contact with eyes or mucous membrane, flush immediately with plenty of warm water and seek medical attention without delay.

### Legal notes

The information, recommendations and application - based on ARACO current knowledge and experience of the products when properly stored, handled and applied under normal conditions. ARACO products are guaranteed against defective materials and manufacture and are sold subject to its standard conditions. Users should always refer to the most recent Technical

**ARACO FOR ADMIXTURES & CONSTRUCTION MATERIALS S.a.I.**

Lebanon, Beirut: Fax: +961 8 512413/ Tel:+961 1 562510

Email: [aacm@araco-group.net](mailto:aacm@araco-group.net) / MOB:+961 3 104539



# ARACO SEAL-CRETE

## High solids acrylic floor and wall sealer and curing compound

Data Sheet for the product concerned, copies of which will be supplied on request.

**ARACO FOR ADMIXTURES & CONSTRUCTION MATERIALS S.a.l.**

Lebanon, Beirut: Fax: +961 8 512413/ Tel: +961 1 562510

Email: [aacm@araco-group.net](mailto:aacm@araco-group.net) / MOB: +961 3 104539