



ARACO SB Bitumen Coating

Solvent Based bitumen primer

Product Description

ARACO SB Bitumen Coating is a quick drying solvent based low viscosity bitumen primer, it is used as a primer coat on masonry and concrete substrates to block superficial dust and porosity and to improve the adhesion of bitumen based membranes and coatings.

ARACO SB Bitumen Coating is low in viscosity, which allows it to penetrate into the concrete pores and improve the adhesion between the membrane and the concrete surface. In addition to that, the primer also acts as a binder for the dust particles which gets accumulated on the concrete surface even after cleaning.

Uses

ARACO SB Bitumen Coating can be used:

- Prior to the application of bitumen based waterproofing membranes and coatings.
- As a curing compound on freshly cast concrete.
- as a waterproof paint on foundation walls,
- as a fixative consolidating primer on cement, wood and metal surfaces

Advantages


- Improves the adhesion between bitumen based sheet membranes and coatings
- Cold applied
- Work as a curing compound on freshly cast concrete.
- Anti-corrosive

Product Data

Appearance	Viscous Black liquid
Density	0.9 ± 0.1 g/cm ³
Solid Content	40 ± 2
VOC	<25g/ltr
Storage life	Store in a dry shaded area at temperature between 10°C and 40°C.
Shelf life	Original Sealed container has a shelf life of 12 months if stored in the right conditions

Legal notes

The information, recommendations and application - based on ARACO current knowledge and experience of the products when properly stored, handled and applied under normal conditions. ARACO products are guaranteed against defective materials and manufacture and are sold subject to its standard conditions. Users should always refer to the most recent Technical Data Sheet for the product concerned, copies of which will be supplied on request.



ARACO SB Bitumen Coat

PACKAGE	15 liters pail
COVERAGE	approx. 5m ² /liter

Standard Compliance

- ASTM D41
- BS EN 3416 type A class C

Surface Preparation

Substrate should be sound, clear, free from loose material, grease, laitance, dirt curing compound, etc. Surfaces must be dry, even and smooth and any imperfections should be repaired by the means of **ARACO REPAIR SYSTEM**.

Application

ARACO SB Bitumen Coating can be stirred and applied using a brush or a spray. It is recommended to apply a minimum of two coats of **ARACO SB Bitumen Coating**. A thick coat can be laid even on vertical surface due to the thixotropic nature of the product. Each layer should be applied at right angle to the previous one to obtain proper uniform coverage. Allow a minimum of 1 hours between coats. in high humidity and cold weather, this period can extend up to 12 hours. Do not apply in wet weather or in direct sunlight.

Safety instructions

Product may cause skin irritation. Wear gloves and goggles and apply barrier cream to hands. In contact with eyes or mucous membrane, flush immediately with plenty of warm water and seek medical attention without delay.

ARACO FOR ADMIXTURES & CONSTRUCTION MATERIALS S.a.l.

Lebanon, Beirut: Fax: +961 8 512413/ Tel: +961 1 562510
Email: aacm@araco-group.net / MOB: +961 3 104539



ARACO SB Bitumen Coating

Solvent Based bitumen primer

ARACO FOR ADMIXTURES & CONSTRUCTION MATERIALS S.a.l.

Lebanon, Beirut: Fax: +961 8 512413/ Tel:+961 1 562510

Email: aacm@araco-group.net / MOB:+961 3 104539